

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Oak

VK/04710/CE/D/W/W/20


White/wood grain. 3000K. 12W. 840lm. ø20cm. AC220-240V. 120°. LED SMD2835. Driver Eaglerise. Ceiling. -20°C → 60°C. 50.000hrs. Dimmable Yes, triac. CRI>80. Metal + PVC. IP20




IP20



Dimensions



Gallery





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	12W
Voltage	AC220-240V
Fitting	Ceiling
Type	Light
Safety class	
Light source	SMD 2835
IP Rating	IP20
CRI	CRI>80
Dimmable	 TRIAC
Lifetime	50.000hrs
Clicks	20,000
Driver	Eaglerise
Working temperature	-20°C-60°C
PAGE	184 New Products 2026
NICKNAME	Oak

Physical Specifications	
Family	Oak
Color	White/wood grain
Material	Metal + PVC
Width	ø20cm
Length	ø20cm
Height	9cm
Net weight of product (kg)	1.10kg
Gross weight with inner box (kg)	1.70kg
Width (inner box)	25cm
Length (inner box)	25cm
Height (inner box)	15cm

Illumination Data	
Lumen	840lm
Beam angle	120°
Lighting direction	

Packing Info	
Pcs/carton	1pc

Certification & Warranty	
Guarantee	2 years