

SINCE 1978



LEADING LIGHT

# Product Datasheet

vkleadinglight.gr

Nook

## VK/04706/B/W


Black. 3000K. 6W. 690lm. LED Bridgelux. Driver Eaglerise. AC220-240V. 28°. Wall/Reading light. ≤35°C. Working life 3 years. Dimmable No. With on/off switch. CRI>80. Aluminum+Iron. IP20




IP20



### Dimensions



### Gallery






### Downloads




## VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	6W
Voltage	AC220-240V
Extra	With ON/OFF switch
Fitting	Wall/Reading
Type	Light
Safety class	
Light source	Bridgelux
IP Rating	<b>IP20</b>
CRI	CRI>80
Dimmable	
Lifetime	3 years
Clicks	5,000
Driver	Eaglerise
Working temperature	<35°C
PAGE	218 New Products 2026
NICKNAME	Nook

Physical Specifications	
Adjustable	
Family	Nook
Color	Black
Material	Aluminum + iron
Width	ø3.9cm
Length	23.6cm
Height	10.9cm
Net weight of product (kg)	0.32kg
Gross weight with inner box (kg)	0.37kg
Width (inner box)	10.5cm
Length (inner box)	25cm
Height (inner box)	8.5cm

## Illumination Data

Lumen	690lm
Beam angle	28°
Lighting direction	

## Packing Info

Pcs/carton	20pcs
------------	-------

## Certification &amp; Warranty

Guarantee	2 years
-----------	---------

## Energy Label



**ENERGY**

VK LEADING LIGHT  
VK/04706/B/W

A  
B  
C  
D  
E  
F  
G

**D**

6  
kWh/1000h

2019/2015