

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr



Mim

VK/04716/B/W/60

Sand Black. 3000K. 1W. 74lm. DC24V. LED Bridgelux. 50.000hrs. Diffuse Light. Dimmable No. -20°C→ 45°C. Outdoor ground. Included Spike & base. CRI>90. 60cm. Aluminum + Acrylic. IP65



IP65    

Dimensions	Gallery	Downloads
	 	  

Technical Specifications	
Kelvin	3000K
Power	1W
Voltage	DC24V
Fitting	Outdoor ground
Type	Light
Safety class	N3
Light source	Bridgelux
IP Rating	IP65
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	-20°C-45°C
PAGE	378 New Products 2026
NICKNAME	Mim

Physical Specifications	
Family	Mim
Color	Sand Black
Material	Aluminum + acrylic
Width	ø2.5cm
Length	ø2.5cm
Height	60cm (+21cm of spike)

Illumination Data	
Lumen	74lm
Beam angle	Diffuse light
Lighting direction	

Packing Info	
Pcs/carton	30pcs

Certification & Warranty	
Guarantee	3 years

Energy Label



VK LEADING LIGHT

VK/04716/B/W/60

A

B

C

D

E

F

G

1

kWh/1000h



2019/2015