

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Mim

VK/04716/RB/W/60


Rust Brown. 3000K. 1W. 74lm. DC24V. LED Bridgelux. 50.000hrs. Diffuse Light. Dimmable No. -20°C→ 45°C. Outdoor ground. Included Spike & base. CRI>90. 60cm. Aluminum + Acrylic. IP65




IP65




Dimensions



Gallery



Downloads



VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	1W
Voltage	DC24V
Fitting	Outdoor ground
Type	Light
Safety class	N3
Light source	Bridgelux
IP Rating	IP65
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	-20°C-45°C
PAGE	378 New Products 2026
NICKNAME	Mim

Physical Specifications	
Family	Mim
Color	Rust brown
Material	Aluminum + acrylic
Width	ø2.5cm
Length	ø2.5cm
Height	60cm (+21cm of spike)

Illumination Data	
Lumen	74lm
Beam angle	Diffuse light
Lighting direction	

Packing Info	
Pcs/carton	30pcs

Certification & Warranty	
Guarantee	3 years

Energy Label

ENERGY

VK LEADING LIGHT

VK/04716/RB/W/60

A

B

C

D

E

F

G

1

kWh/1000h



2019/2015

F