

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

CRi90

VK/24/2216W/927/60


Ledstrip SMD 2216 EPISTAR, 24V, 6W/m, 697lm/m, 2700K, 5m/roll, CRI>90, IP66



IP66



Dimensions




Gallery



LED Stripa CRi90, 24V

24V	6W/m	697lm/m	2700K	5m/roll	CRi>90	IP66
-----	------	---------	-------	---------	--------	------




Downloads



VK Leading Light

Since 1978

Technical Specifications	
Kelvin	2700K
Power	6W/m
Voltage	24V
Fitting	Ledstrips
Type	Light
Light source	SMD 2216 EPISTAR
Number of LED	60pcs/m
IP Rating	IP66
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Meters	5m/roll
Working temperature	-10°C - 40°C
Storage temperature	-20°C - 60°C
PAGE	64 Technical 2024
NICKNAME	CRI90

Physical Specifications	
Width	13mm
Length	5m
Net weight of product (kg)	0.2935
Gross weight with inner box (kg)	0.4335
Gross weight with master box (kg)	9.31
Cut out	every 100mm

Illumination Data	
Lumen	697lm/m

Packing Info	
Pcs/carton	20pcs

Certification & Warranty

Guarantee	5 years
-----------	---------

Energy Label

The image shows an energy label for a VK LEADING LIGHT. At the top left is the European Union flag and the word "ENERGY" with a lightning bolt icon. Below this, the text "VK LEADING LIGHT" and the model number "VK/24/2216W/927/60" are displayed. The central part of the label features a vertical scale of energy efficiency classes from A to G, represented by colored arrows pointing right. Class A is green, B is light green, C is yellow-green, D is yellow, E is orange-yellow, F is orange, and G is red. A black arrow points to class F. Below the scale, the energy consumption is listed as "30 kWh/1000h". To the right of this text is a QR code and the date "2019/2015".