




PROJECT
TYPE
NOTES
QUANTITY
DATE


Rectangular shaped wall surface luminaire made from aluminium; Gold wet painted; brushed; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

GENERAL

Wall
Surface
Gold
IP20
Interior
1540 lm
CIE flux code: 56 84 97 50 100

LIGHT DISTRIBUTION

LED


2700 K
CRI ≥ 90
L80 / 90000 h
initial MacAdam ≤ 3 SDCM

ELECTRICAL

phase-cut dim
220 - 240 V
system 31 W
Class 1

PHYSICAL

length 900 mm
width 32 mm
height 80 mm
2.01 kg




Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.93	0.91	0.89
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMFa	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMFa ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.